


achieved by Fred Goulding, Donald Landis, Cerny and Richard Pehl, who used it to demonstrate the existence of He^8 . The method uses several semiconductor detectors to measure the energy loss rate and total energy of nuclei ejected from the target with a circuit that identifies charges and mass numbers of the nuclei. By measuring the energy losses in two separate transmission detectors and thereby getting two separate identifications of each event, the Berkeley experimenters acquire improved isotopic resolution; they reject events in which the two identifications do not agree.

Among the isotopes identified are He^6 , and He^8 , Li^9 and Li^{11} , and B^{14} and B^{15} . These nuclides are all particle stable; they decay only through weak-interaction processes by beta emission with relatively long half-lives measured in the tens of milliseconds. Some predictions by Gerald Garvey and Itzak Kelson suggested the existence of B^{14} and B^{15} but L^{11} was predicted to be particle unstable.

The significance of the work at LRL, Poskanzer stated, is twofold. First, the determination of which nuclei are particle stable and which are particle unstable sets certain limits on their masses that are useful in testing mass relations. For instance, the particle stability of Li^{11} indicates that its mass is at least 2.5 MeV lower than the most reliable prediction. Thus, one has the surprising result that the configuration of three protons and eight neutrons appears to be considerably more stable than one would predict by extrapolation from nuclei closer to beta stability.

The second reason is in the demonstration of the technique developed for the identification of nuclei. The accompanying graph demonstrates the type of identification now possible. It shows all the isotopes from Li^6 to C^{15} with the exception of only C^9 . This technique has application in fields such as cosmic-ray and heavy-ion studies. In particular the LRL group will study the details of the production of these nuclei at the Bevatron to determine whether a fragmentation or an evaporation mechanism is a better description for their production.

It is almost as interesting to note the isotopes which did not appear, for example Li^{10} and Be^{13} . These are



ENERGY-LOSS SPECTRUM obtained with multichannel analyzer shows a peak for every isotope produced in the proton scattering process.

predicted to be particle unstable by Garvey and Kelson and there is no trace of them in the energy-loss spectrum.

3-km Radio Telescope to be Built by Univ. of Maryland

A unique radio telescope with an aperture of over 3 km is being built by the University of Maryland at Clark Lake near Borrego Springs, Calif. The construction, which will take approximately two years, is being supported by the National Science Foundation and the Maryland school.

Its design is quite different from the radio telescopes now in use. Approximately 1000 individual antennas will stretch across the dry lake bed in the shape of a large T. The Maryland telescope will be fully steerable even though it will have no moving parts. Instead of a mechanical tracking system, sophisticated electronics will be used to steer the device. This unique characteristic will help radio telescopists detect many weak sources in the decimeter range and monitor more than one radio source simultaneously. William Erickson, the project director, said that this new instrument will be the first steerable array telescope of its kind. It is comparable to a dish-type telescope with a 3-km diameter; at present the largest dish radio telescopes have diameters of 183 to 305 meters.


Planned projects for the Maryland

radio telescope include cataloging and measuring 8000 known extragalactic radio sources to better understand the mechanism of radio emission. A study of supernova remnants, believed to be an important source of cosmic rays, also will be undertaken. Other research will include solar observations that should produce a complete picture of the sun's radio emissions each second, measurements of the scattering of radio waves in the solar corona and correlation of this information with that obtained optically from spacecraft or balloons.

The radio telescope will also monitor the planet Jupiter, as yet the only positively identified planetary radio source emitting decimeter wavelengths. Because of the sensitivity of the new telescope similar radio signals emanating from other planets may be found.

JPL Suggests Bouncing Off A Planet to Reach Another

Space-age Tarzans will substitute gravity for vines. Just as the Jungle Boy uses the tension in a conveniently placed suspension to lose potential energy he doesn't want and gain a momentum directed toward the place he wants to reach, interplanetary explorers should use gravitational acceleration from appropriately placed planets to whip them around into the trajectory they need. So says Gary Flandro of Jet Propulsion Laboratory, who has



Time sharing marches on... PDP-10 is still the leader.

DIGITAL started time-sharing some time ago. With the PDP-6. Hardware and software. PDP-10 is our second step.

The reason that's important is this: our first step is behind us. Two years' continuous work on the software. Nearly two dozen installations using it. Improving it. Refining it. That's all done.

When the PDP-10 hardware arrives in September (five versions, five software packages, upwards compatible, truly modular), it will be more than cabinets filled with electronics. It will be a working, problem-solving, 36-bit word, 1 μ sec, expandable, scientifically oriented computing system with memory from 8 to 262 thousand words.

Two of those versions will offer time-sharing. Second generation time-sharing. Complete, general purpose, simultaneous

multisusage, "time-slicing", "time-splicing" time-sharing.

Disc swapping. Batch processing. And in the hardware, 365 powerful instructions. 16 general purpose registers. 7 fully nested interrupt levels. 16 accumulators. 15 index registers. High speed multiplexer channels. 64 programmed operators. Modular mnemonics. Flexible I/O bus structure. Programmed priority-interrupt system. All 16 Boolean operations, each in four modes.

PDP-10 is big. Powerful. In the several million dollar class just a few years ago. But it's little, too. Little enough for a scientist to put the system on-line with his experiment as his personal research tool. Little enough for a physics department with time-sharing needs. And little in price, too. Nearest competitor wants 50% more. Write.

digital
COMPUTERS • MODULES

DIGITAL EQUIPMENT CORPORATION, Maynard, Massachusetts 01754. Telephone: (617) 897-8821 • Cambridge, Mass. • New Haven • Washington, D.C. • Parsippany, N.J. • Rochester, N.Y. • Philadelphia • Huntsville • Pittsburgh • Chicago • Denver • Ann Arbor • Houston • Los Angeles • Palo Alto • Seattle • Carleton Place and Toronto, Ont. • Reading, England • Paris, France • Munich and Cologne, Germany • Sydney and West Perth, Australia. Modules distributed also through Allied Radio

computed some journeys you can make that way in the 1970's.

Take Neptune. A direct flight with today's launchers might require more than 30 years. But in 1978 planets will be arranged so that you can swing through the trees from earth to Jupiter to Saturn to Uranus and finally to Neptune—all in less than 9 years. Other similar flights are possible. You can swing off Jupiter to the sun in 2.6 years if you launch in April 1973, leave earth in October 1978 and go by way of Jupiter either to Saturn in 2.8 years or to Uranus in 5.9 years, or use Jupiter as your suspension point and reach Neptune in 8.1 years after a November 1979 start.

Solar-panel-powered ion engines would be aboard the vehicle to permit redirecting the flight at each planetary encounter. It appears that fly-by missions with such a system could use launchers no bigger than the Atlas Centaur.

Transuranium Facility at HVEC to Have Two Tandems

High Voltage Engineering Corp. is making plans for an installation that will study heavier-than-uranium elements. As indicated in the drawing, it would use two tandem Van de Graaff accelerators in series to accelerate heavy ions (up to multiply charged uranium) and hurl them at heavy target nuclei to create atoms heavier than those of the 104 elements observed so far. Particular goals would be atoms


$^{114}\text{X}^{298}$ and $^{126}\text{X}^{310}$, one of which might be doubly magic and have an unusually long half-life, perhaps as long as 10 years. Intentions are to put the facility into operation at Burlington, Mass., by 1 Jan. 1970. Until other transuranium accelerators are available, HVEC would operate the facility for a group of agency-supported scientists. Thus it would become, for a limited time, a kind of privately operated "national lab."

Funds for the project would come partly from HVEC (\$4.2 million for construction) and partly from "a funding agency" (\$1 million for construction, \$0.8 million for operation).

Accelerated ions would start out from a newly designed diode source negatively charged, pass through a model MP tandem with several strippers and get their final acceleration as positive ions in a new tandem, a model XTU. Experiments would occur in the high-voltage terminal at the center of the XTU.

The diode source can inject ion currents ranging from $5\mu\text{A}$ of uranium to $500\mu\text{A}$ of hydrogen. The MP accelerator would have a 16-MV terminal potential and five solid gas strippers so that uranium ions emerging from it would have a 450-MeV kinetic energy and a most probable positive charge of 50. From the spectrum a cross-field analyzer would select ions, and then they would be accelerated to the terminal of the XTU, first of a new generation of tandem accelerators with its terminal at 20 MV. Thus uranium ions at the XTU terminal would have 1450-MeV energy and

TWO TANDEM VAN DE GRAAFFS in series will accelerate heavy ions.



Expanded versatility in reversible counters



Now two new options for the Hewlett-Packard 5280A Reversible Counter add to its measurement capabilities:

1. An internal time base permits precise setting of gating period in discrete increments as small as 1 msec, with front-panel setting. This means that besides straight totalizing, you can now measure frequency or normalize your readings.

2. A special "Readout on the Fly" feature allows you to record measurements at any instant without interrupting the count. This is achieved by transferring your count to an internal storage register. Time between recording commands can be as short as 1 msec, making the 5280A useful in information or control system work without retarding system speed.

These new options PLUS:

- six operating modes, including modes for interferometer fringe counting;
- 2 MHz counting rate, up or down;
- reversal in $0.25\mu\text{sec}$;
- adds or subtracts (1 MHz rate for each channel);
- stable, wide-range trigger input level controls.

The standard 5280A with the 5285A Universal Plug-in costs \$1900. Options are extra.

A 40-page Application Note (AN #85) is now available without charge—"Using A Reversible Counter." Call your local HP field engineer or write Hewlett-Packard, Palo Alto, Calif. 94304. Europe: 54 Route des Acacias, Geneva.

HEWLETT  PACKARD