

atoms relaxes to about 100 eV. If a collision sequence intersects the surface before it runs out of steam an atom may be ejected, with a maximal energy related to the energy needed to start the focused-collision sequence.

In their experiments Politiek, Rol, Los and Ikelaar used a rotating velocity selector and platinum-tungsten alkali-beam detector to record the intensity and velocity distribution of their potassium beam; they measured a peak current of 2.5×10^{-13} amp and an energy range of 0.5–45 eV (velocity 1000–15 000 meters/sec).

2nd ESRO Satellite Of Year To Study Polar Ionosphere

The second satellite launched by the European Space Research Organization this year achieved polar orbit 3 Oct. Eight experiments on board the

84-kg craft are measuring energies and angles of particles striking the polar ionosphere, the resulting projection of visible light, and changes in the electron and ion density and temperature distribution.

Experiments were prepared in Norway, Sweden and the United Kingdom. Other ESRO members are Belgium, Denmark, France, West Germany, Italy, the Netherlands, Spain and Switzerland (Norway is not a member). Prime contractor for the satellite was the Laboratoire Central de Télécommunications, a French associate of International Telephone and Telegraph. NASA launched it with a four-stage Scout rocket from Lompoc, Calif.

Originally scheduled for launch in 1967, the satellite is known as ESRO I (it has been renamed Aurora since launch). ESRO IIA, launched 29 May 1967, was lost in the South Pacific when the third stage failed. ESRO

IN BRIEF

Three more pulsars have been added to the catalog by teams at Arecibo and Jodrell Bank. The Arecibo group found the tenth (with a period of 0.56 sec) in late August and the 11th (period 0.53 sec) in late September. The 12th, Jodrell Bank's first, was reported in late October to have a 0.36-sec period.

A 500-keV electron microscope went into operation at the University of Virginia 3 Oct. The School of Engineering and Applied Science will use the RCA instrument in materials science, medical studies, chemistry and physics.

A satellite with infrared and visible-light cameras has been proposed by the Interior and Agriculture Departments to provide information on the distribution of vegetation, surface and ground water. Future remote sensors would include radar and microwave spectrometers.

Calibration service for measuring effective noise temperature of noise sources in four additional waveguide sizes are now available from the Radio Standards Engineering Division of the National Bureau of Standards in Boulder. The long dimension of the rectangular cross sections of the waveguides (and their frequency range) are 7.2 cm (2.60–3.95 GHz), 1.9 cm (10.0–15.0 GHz), 5.8 cm (3.30–3.95 GHz)

and 2.8 cm (8.2–10.0 GHz).

Notre Dame University has begun research with its 15-MV FN tandem Van de Graaff accelerator. The National Science Foundation funded the purchase from High Voltage Engineering Corp.

A cryogenic-flow research facility has been established in the metrology division of the National Bureau of Standards. A cryogenic flow loop with dynamic gravimetric mass flow calibration allows study of fluid metering over a wide range of temperatures and pressures.

Effects of severe earthquakes and volcanic eruptions on a small Antarctic island will be measured this month by US scientists operating from a new research vessel, the Hero. Other programs planned for the Antarctic summer just beginning include analysis of the physical properties and crystal structure of 2165-meter ice cores, measurement of cosmic-ray flux, and studies of gravitational and magnetic fields.

CORRECTION: Lawrence Radiation Laboratory at Livermore is negotiating to purchase a tandem accelerator as part of a "Cyclo-Graaff" combination, and the tandem is expected to be operational in late 1970. An earlier report (PHYSICS TODAY, September, page 75) said the tandem already existed.



TIRED OF WAITING FOR YOUR GE(Li)?

- Fed up with broken promises from "Do-it-yourself" detector makers at your lab?
- How long have you been waiting for "Brand X" to deliver?
- Disillusioned with specifications in wide variance with what you ordered?

FROM NUCLEAR DIODES: IMMEDIATE DELIVERY ON STOCK DETECTORS WITH KNOWN SPECIFICATIONS

Get on our distribution list for our bi-weekly published stock list of planars, trapezoidal and true coaxials. Some are already mounted in a variety of cryostats or you may select one of your choice from our catalog. System resolutions range from 2.5 to 6.0 keV for Co⁶⁰. Sizes from smallest planar to largest coaxials. Check the list, pick the performance and price that meet your needs and take delivery NOW.

P.S. Send for a free copy of our new manual "The Selection and Use of Ge(Li) Detectors."

**nuclear
diodes inc.**
box 135, prairie view, illinois 60069
Phone: 312-634-3870