

winning election as a fellow of the American Physical Society.

Glockler was also the retired chief scientist of the Army Research Office in Durham.

Pioneer in Ultrasonics;

Egon A. Hiedemann

A professor emeritus at Michigan State University, Egon T. Hiedemann died on 8 Feb. Hiedemann was known for his work on optical methods for research in ultrasonics.

Studying at the Universities of Heidelberg, Bonn, Berlin and Goettingen, he taught at the University of Cologne from 1922-40. Before coming to the US as a consultant to the Engineering Research and Development Laboratory at Fort Belvoir, Va., he was dean of the School of Science and Arts at Karlsruhe Technical University. He joined the MSU faculty in 1950 as professor and chairman of the physics and astronomy department.

Richard G. Nuckolls, 54;

Was Parsons Chairman

Richard G. Nuckolls, chairman of the physics department at Parsons College, Fairfield, Iowa, died 14 Feb. of a heart attack. He was 54 years old.

A graduate of Oberlin, Nuckolls had taught at Cornell Aeronautical Laboratory, Kansas State College and the State University College at Cortland, N.Y., before moving to Parsons in 1965. He was a native of Grinnell, Iowa.

W. Adair Morrison, 56;

Research Administrator

W. Adair Morrison, a research administrator who worked in both Canada and the US, died 19 Feb. in Ottawa after a long illness. He had left his post as a project analyst at General Electric last year after 12 years to join the staff of the delegate general for policy and planning of the National Research Council of Canada.

Born in Saskatchewan, Morrison lived in China briefly as a child. He took his BS and MA at the University of Saskatchewan and his PhD at McGill. After teaching school in Saskatchewan and Quebec, he joined the radiology section of the National Re-

Indispensable—MCL's NEW, **HIGH POWER PULSE MODULATOR**

**Series
10299B**



- **Choice of three standard adjustable output voltage ranges:** 0-1.5 KV @ 6.0 amperes, peak; 0-3.0 KV @ 3.0 amperes, peak; or 0-6.0 KV @ 1.5 amperes, peak. (Models with other voltages and currents at average power levels to 100 watts, available on special order.)
- **Peak output voltage readout,** accurate to 2.0% of full scale, from 100 pulses per second up.
- **Pulse characteristics:** Width: adjustable, 0.5 to 10 microseconds. Droop: 8.0%, maximum at 10 microseconds' width. Overshoot at rated output: 12%, maximum. Rise time: 170 nanoseconds, nominal. Fall time: 200 nanoseconds, nominal. Repetition rate: adjustable, 100 Hz to 12 kHz.
- **Duty cycle readout:** .001 to .01, with 2.0% accuracy.
- **Overload cut-off:** adjustable over same range.

ADDITIONAL FEATURES, SPECIFICATIONS

- Positive or negative, output pulse polarity
- Internal or external triggering (external: + 2.0V into 75 ohms)
- Input power, 115 VAC, 50/60 Hz @ 300 watts
- Dimensions: 14" x 8½" x 11"
- Weight: 35 lbs., approx.

Write for descriptive brochure, and MCL's new catalog describing "Dynamic Disciplines" products.

MICROWAVE CAVITY Laboratories, Inc.
Division of K M S Industries, Inc.



10 North Beach Avenue
La Grange, Illinois 60525
Phone: (312) 354-4350
Western Union Telex: 25-3608

Producers of quality, high power RF, CW and pulse amplifier systems-subsystems; klystron amplifiers; solid state components; test equipment; accessories.