

exciting electromagnetic field induces in the shell a series of multipole moments that effectively cancel some of those of the object inside it. But the properties of the object being cloaked and of the cloak itself would have to be carefully matched. The scheme thus lacks the generality that Schurig and his colleagues achieved: In their device anything—from mouse to missile—can be cloaked, provided it fits within the cloak's dimensions.

Romulan dreams

Because the cloak is dispersive—as it must be since the phase velocity of waves inside the cloak exceeds the speed of light in free space—the bandwidth over which it works well is narrow; Schurig and coworkers performed their proof-of-principle demonstration at a single frequency of 8.5 GHz. The microwave-frequency region has plenty of relevance in today's world, though, and one can imagine an eventual replacement to radar evasion and stealth technologies in aircraft—à la Romulan cloaking of *Star Trek* fame. According to the University of Rochester's Allan Greenleaf and col-

leagues, invisibility is not restricted to passive objects. Active sources and sinks—cell phones and computers, say, or anything else that emits or receives a signal—may also be cloaked, at least in principle.⁶

Metamaterials based on a nonresonant circuit design might overcome the bandwidth problem to some degree. But extending the response to optical frequencies is trickier. Today the nanometer-scale lithography required to shrink circuit components to fractions of the wavelength of visible light is routine. But the electric permittivity of metals at optical frequencies is several orders of magnitude lower than it is in the microwave region. Electrons simply can't follow the oscillations in the electric field nearly as well at such high frequencies.

Creating 3D cloaks isn't easy either. The difficulty lies in designing a cloak's configuration to produce all the needed variations in the tensor components of ϵ and μ . Traditional metamaterials are assembled from 2D planar sheets that typically intersect each other in a cubic lattice. The Duke–Imperial College design veered from tradition by bending

sheets into cylinders to form a metamaterial that is semicrystalline—periodic in θ and z but amorphous in the radial direction. The next-generation design may incorporate spherical circuit configurations and more exotic topologies. But according to Pendry, that shouldn't surprise us. "The more you think about Maxwell's equations, the more you realize that geometry is at their heart."

Mark Wilson

References

1. J. B. Pendry, A. J. Holden, D. J. Robbins, W. J. Stewart, *IEEE Trans. Microwave Theory Tech.* **47**, 2075 (1999).
2. J. B. Pendry, D. Schurig, D. R. Smith, *Science* **312**, 1780 (2006).
3. D. Schurig, J. J. Mock, B. J. Justice, S. A. Cummer, J. B. Pendry, A. F. Starr, D. R. Smith, *Science* **314**, 977 (2006).
4. U. Leonhardt, *Science* **312**, 1777 (2006); U. Leonhardt, T. G. Philbin, *New J. Phys.* **8**, 247 (2006).
5. A. Alù, N. Engheta, *Phys. Rev. E* **72**, 016623 (2005). See also G. W. Milton, N.-A. P. Nicorovici, *Proc. R. Soc. A* **462**, 3027 (2006).
6. A. Greenleaf, Y. Kurylev, M. Lassas, G. Uhlmann, <http://arxiv.org/abs/math/0611185v1>.

researchers showed that the coupling is 100% efficient; no atoms are lost during extraction and transport along a 1-mm guide. The new atom laser opens promising prospects for applications in atom interferometry and more fundamental studies of matter-wave propagation. (W. Guerin et al., *Phys. Rev. Lett.* **97**, 200402, 2006.) —PFS

A prism for x rays. With far more energy than visible light, x rays reflect from surfaces only at glancing angles and with little wavelength-dependent spreading. Bragg diffraction in a crystal allows for scattering of x rays through larger angles because the incoming x rays scatter from numerous atomic planes beneath the surface. With a normally cut crystal, though, there is still little dispersion. Physicists using the Advanced Photon Source at Argonne National Laboratory have now spread out a beam of x rays into a rainbow of colors with the help of an asymmetrically cut crystal, whose atomic planes are not parallel to the crystal surface. The effect is strongest when the reflecting atomic planes are nearly perpendicular to the surface; then exact backscattering occurs not at normal incidence to the planes but at an angle that depends on the x-ray energy. The diffracted x-ray beam is spread out prismatically into its component wavelengths. In the experiment, an incoming beam of 9-keV x rays with angular spread of only 1 microradian was backscattered into a rainbow with an angular dispersion of 230 μ rad. According to team leader Yuri Shvyd'ko, the new technique can lead not only to a new type of x-ray monochromator and to very-high-resolution x-ray spectrometers but also to compression of x-ray pulses in time. (Y. V. Shvyd'ko et al., *Phys. Rev. Lett.* **97**, 235502, 2006.) —PFS

A piconewton force sensor. Many forces in the world of cell biology are at the piconewton (10^{-12} N) level. Examples include the force applied by the kinesin molecular motor protein to

transport vesicles (6 pN), the force needed to unzip a DNA molecule at room temperature (9–20 pN), and the force needed to rupture a DNA molecule by pulling on opposite ends (65 pN). Biophysicists need a cost-effective force sensor in this range that works reliably in water and other solvents, and Steven Koch and his colleagues at Sandia National Laboratories are working on one. The core of their device is a spring 0.5 mm long but only a micron thick, fabricated using a standard micromachining process and having a spring constant of about 1 pN/nm. (The figure shows a stiffer and shorter—186 μ m long—spring between the combs.) Mounted on a substrate, the spring can be used in a number of ways: For example, it can be entrained to move with the push or pull of a biological sample, or it can be made sensitive to magnetic fields and function as a field sensor. It is also relatively insensitive to its environment, including temperature and solvent. The displacement of the spring is currently viewed with 2-nm precision by a video camera, but faster and more precise methods are possible. Koch says the most likely applications of the new sensor will be to measure forces on magnetic microspheres used in single-biomolecule experiments and to calibrate the electromagnets used in deploying microspheres. The Sandia sensor could also be adapted to apply an adjustable tension to single DNA molecules in order to study protein binding or enzymatic processes. (S. Koch, G. E. Thayer, A. D. Corwin, M. P. de Boer, *Appl. Phys. Lett.* **89**, 173901, 2006.) —PFS ■

